

Principle Parameters

MODEL #	Description	Power (W/h)		CCT (K)	Luminous Flux (lm)	
		Rated	System		Initial	Mean
FD31021-WQ5	310 x 140 x 355mm, 63W cool white	49W	63W	6500-7000K	3822	3440
FD31024-WQ5	310 x 140 x 355mm, 72W cool white	56W	72W		4368	3930
FD31027-WQ5	310 x 140 x 355mm, 81W cool white	62W	81W		4914	4423
FD31036-WQ5	310 x 140 x 415mm, 108W cool white	83W	108W		6552	5897
FD31045-WQ5	310 x 140 x 505mm, 135W cool white	104W	135W		8190	7371
FD31054-WQ5	310 x 140 x 585mm, 162W cool white	125W	162W		9828	8845
FD31063-WQ5	310 x 140 x 655mm, 189W cool white	146W	189W		11466	10319
FD31021-LP3	310 x 140 x 355mm, 63W neutral white	49W	63W	2700-3200K	2583	2325
FD31024-LP3	310 x 140 x 355mm, 72W neutral white	56W	72W		2952	2657
FD31027-LP3	310 x 140 x 355mm, 81W neutral white	62W	81W		3321	2989
FD31036-LP3	310 x 140 x 415mm, 108W neutral white	83W	108W		4428	3985
FD31045-LP3	310 x 140 x 505mm, 135W neutral white	104W	135W		5535	4982
FD31054-LP3	310 x 140 x 585mm, 162W neutral white	125W	162W		6642	5978
FD31063-LP3	310 x 140 x 655mm, 189W neutral white	146W	189W		7749	6974
FD31021-LP2	310 x 140 x 355mm, 62W warm white	49W	63W	2600-2875K	2415	2174
FD31024-LP2	310 x 140 x 355mm, 72W warm white	56W	72W		2760	2484
FD31027-LP2	310 x 140 x 355mm, 81W warm white	62W	81W		3105	2795
FD31036-LP2	310 x 140 x 415mm, 108W warm white	83W	108W		4140	3726
FD31045-LP2	310 x 140 x 505mm, 135W warm white	104W	135W		5125	4613
FD31054-LP2	310 x 140 x 585mm, 162W warm white	125W	162W		6210	5589
FD31063-LP2	310 x 140 x 655mm, 189W warm white	146W	189W		7245	6521

NOTES:

1. The standard color rendering index of LED is ≥ 75 .
2. Models of LED driver are subject to change for better performance as and when necessary. 110VAC LED drivers are available on customers' request.