



ELITA 500 Circular Recessed Downlight Series

An in-line type circular recessed downlights with stationary drum housing suitable for seamless high ceiling exceeding 3 meters casting downward. Constant current LED driver is attached to the drum externally. Three type of ceiling-hole are available, Ø160 (6 inches); Ø190mm (7.5 inches); and Ø224mm (8.8 inches). Standard trim color available in either white or ivory-white color.

Principle Parameters

Model #	Power (W)		CCT (K)	LED Driver*		Basic Measurement (mm)		
	Rated	System		Model	DC Output	Trim	Chimney	Ceiling
529-03LP3	7.0	9.0	3000~3500	MU38-3	10V/0.7A	Ø190	Ø105	Ø160
529-03WQ5	7.0	9.0	5500~6000					
529-04LP3	9.4	12.0	3000~3500	MU38-2	14V/0.7A	Ø190	Ø105	Ø160
529-04WQ5	9.4	12.0	5500~6000					
529-05LP3	11.7	15.0	3000~3500	MU38-1	21V/0.7A	Ø190	Ø105	Ø160
529-05WQ5	11.7	15.0	5500~6000					
529-06LP3	14.0	18.0	3000~3500	MU38-1	21V/0.7A	Ø190	Ø105	Ø160
529-06WQ5	14.0	18.0	5500~6000					
530-09LP3	21.0	27.0	3000~3500	JA30700	15V/0.7A	Ø230	Ø105	Ø190
530-09WQ5	21.0	27.0	5500~6000					
530-12LP3	28.0	36.0	3000~3500	JA45700	45V/0.7A	Ø230	Ø105	Ø190
530-12WQ5	28.0	36.0	5500~6000					
531-12LP3	28.0	36.0	3000~3500	JA45700	45V/0.7A	Ø 265	Ø125	Ø224
531-12WQ5	28.0	36.0	5500~6000					
531-15LP3	35.0	45.0	3000~3500	JA45700	45V/0.7A	Ø 265	Ø125	Ø224
531-15WQ5	35.0	45.0	5500~6000					

* We reserve the right to change the LED drivers for better performances.