



ELITA 560 Circular Recessed Downlight Series

A sidelong type circular recessed downlights attach with electrical box. The model is suitable for ceiling of any height.

There are six sizes of ceiling-hole ranging from Ø90mm (3.6") to Ø230mm (9.0") are available. Standard trim color available in white, ivory-white and nickel plated finished.



Principle Parameters

Model #	Power (W)		CCT (K)	LED Driver*		Basic Measurement (mm)		
	Rated	System		Model	DC Output	Trim	Chimney	Ceiling
562-03LP3	7.7	9.0	3000~3500	MU38-3	10V/0.7A	Ø90	Ø72	Ø78
562-03WQ5	7.7	9.0	5500~6000					
563-03LP3	7.7	9.0	3000~3500	MU38-3	10V/0.7A	Ø110	Ø78	Ø85
563-03WQ5	7.7	9.0	5500~6000					
564-04LP3	10.2	12.0	3000~3500	MU38-2	14V/0.7A	Ø143	Ø110	Ø125
564-04WQ5	10.2	12.0	5500~6000					
564-05LP3	12.8	15.0	3000~3500	MU38-1	21V/0.7A	Ø143	Ø110	Ø125
564-05WQ5	12.8	15.0	5500~6000					
565-04LP3	10.2	12.0	3000~3500	MU38-2	14V/0.7A	Ø180	Ø110	Ø160
565-04WQ5	10.2	12.0	5500~6000					
565-05LP3	12.8	15.0	3000~3500	MU38-1	21V/0.7A	Ø180	Ø110	Ø160
565-05WQ5	12.8	15.0	5500~6000					
565-06LP3	15.3	18.0	3000~3500	MU38-1	21V/0.7A	Ø180	Ø110	Ø160
565-06WQ5	15.3	18.0	5500~6000					
566-07LP3	17.9	21.0	3000~3500	MU38-1	21V/0.7A	Ø190	Ø115	Ø175
566-07WQ5	17.9	21.0	5500~6000					
566-08LP3	20.4	24.0	3000~3500	JA30700	30V/0.7A	Ø190	Ø115	Ø175
566-08WQ5	20.4	24.0	5500~6000					
566-09P3	23.0	27.0	3000~3500	JA30700	30V/0.7A	Ø190	Ø115	Ø175
566-09Q5	23.0	27.0	5500~6000					
568-09P3	23.0	27.0	3000~3500	JA30700	30V/0.7A	Ø230	Ø125	Ø210
568-09Q5	23.0	27.0	5500~6000					
568-12P3	30.6	36.0	3000~3500	JA45700	45V/0.7A	Ø230	Ø125	Ø210
568-12Q5	30.6	36.0	5500~6000					