



ELITA™ 720 Circular Recessed Downlight Series

This series is designed as general and ascent luminaire. It is an in-line type circular recessed downlight c/w external constant current LED driver. Ceiling-hole sizes available in Ø75mm (3 inches), Ø100mm (4 inches) and Ø127mm (5 inches). The aesthetic aluminum housings are anodized in either silver or black or such other color as may be requested by customers.

Principle Parameters

Model #	Power (W)		CCT (K)	LED Driver*		Basic Measurement (mm)		
	Rated	System		Model	DC Output	Trim	Chimney	Ceiling
720-03P3	7.7	9.0	3000~3500	MU38-3	10V/0.7A	Ø 90	Ø 70	Ø 75
720-03Q5	7.7	9.0	5500~6000					
723-03P3	7.7	9.0	3000~3500	MU38-3	10V/0.7A	Ø105	Ø 87	Ø 90
723-03Q5	7.7	9.0	5500~6000					
725-04P3	10.2	12.0	3000~3500	MU38-2	14V/0.7A	Ø140	Ø125	Ø135
725-04Q5	10.2	12.0	5500~6000					
725-05P3	12.75	15.0	3000~3500	MU38-1	21V/0.7A	Ø140	Ø125	Ø135
725-05Q5	12.75	15.0	5500~6000					
725-06P3	15.3	18.0	3000~3500	MU38-1	21V/0.7A	Ø140	Ø125	Ø135
725-06Q5	15.3	18.0	5500~6000					

* We reserve the right to change the LED drivers for better performances.

